Safety Data Sheet (SDS)

Products

Part Number	Name	Used in	Remarks
202-32007-30	KRS-5 10cm gas cell		

KRS-5 window

1.	Identification	Product name:	KRS-5 10cm gas cell
		Company:	Shimadzu Corporation
		Address:	1, Nishinokyo-Kuwabaraco, Nakagyo-ku, Kyoto 604-8511
			JAPAN
		Responsible department:	Spectroscopy Business Unit,
			Analytical & Measuring Instrument Div.
		Telephone:	+81-75-823-1203
		Fax:	+81-75-823-4614
2.	Hazards	Classification of the substance	Class 6.1 Poison.
	identification	or mixture	Very toxic by ingestion with cumulative effects. Harmful in
			contact with skin. Toxic to aquatic organisms, may cause
			long term adverse effects in the aquatic environment.
			Particular care must be exercised when machining and
			creating dust or particles. Dangerous for the environment.
		Signal Word: Danger	
		H300	Fatal if swallowed
		H330	Fatal if inhaled
		H373	May cause damage to organs through prolonged or
			repeated exposure.
		Signal Word: Warning	
		H411	Toxic to aquatic life with long lasting effects
		Precautionary Statements:	
		P260	Do not breathe dust/fume/gas/mist/vapors/spray.
		P264	Wash thoroughly after handling.
		P270	Do not eat, drink or smoke when handling this product
		P273	Avoid release to the environment.
		P301+P310	IF SWALLOWED: Immediately call a poison center or
			doctor. Rinse mouth.
		P304+P312	IF INHALED: Call a poison center or doctor/physician if you
			feel unwell.

	Composition			¥2
3.	Composition/ information on	Substance/mixture: Components:	Mixture KRS-5/Thallium Bromide and	I Thallium Iodide
	ingredients	Components: Percent: CAS Number: Chemical Formula: Notice Through Official	Thallium lodide 58% 7790-30-9 TII	Thallium Bromide 42% 7789-40-4 TIBr
		Gazettes Reference Number ENCS: ISHL: 	(1)-1169 Not listed	(1)-1169 Not listed
4.	First-aid measures	Inhalation:	Remove to fresh air. Per breathing has stopped. When trained personnel may admir person warm and at rest. Obt Wash thoroughly with soap a	breathing is difficult, properly nister oxygen. Keep affected ain medical attention.
		Skin: Eyes:	towel. Remove contaminated before re-use. Irrigate thoroughly with wat Obtain medical attention.	
		Ingestion:	Do not induce vomiting. Was water and give 2 cups of v carbonated drinks. Never giv	water to drink. Do not give
5.	Fire-fighting measures	Extinguishing media: Special hazards arising from the substance or mixture: Advice for firefighters:	This product does not burn. Material may evolve toxic fun Use breathing apparatus if ne	
6.	Accidental release measures	Personal precautions, protective equipment and emergency procedures: Environmental precautions: Methods and materials for containment and cleaning up: Reference to other sections	Wear suitable protective clo under Section 8. Avoid makin Prevent further leakage or spi drains. Do not discharge to th Take up and containerize for p any cleaning materials used f Dispose as in Section 13.	g dust. llage. Do not let product enter ne environment. proper disposal. Containerize

7. Handling and storage Precautions for safe handling: Keep away from heat. Avoid contact with skin and e Protect against physical damage. Avoid generating du Keep away from foodstuffs. Keep away from acids strong bases. 9. Physical and chemical Enginearing controls: Install a closed system or local exhaust as possible so workers should not be exposed directly. Also install so shower and eye bath. 9. Physical and chemical Appearance: Frosteventilition: Protecting and the product. 9. Physical and chemical Appearance: First point: Red geometric shapes, no odor. 9. Physical and chemical Appearance: First point: Not Applicable
Conditions for safe storage, including any incompatibilities: Specific end uses:Keep away from foodstuffs. Keep away from acids strong bases. Optical Material for Manufacture of Optical Component optical Component workers should not be exposed directly. Also install se shower and eye bath. Thallium lodide Not set upInstall a closed system or local exhaust as possible so workers should not be exposed directly. Also install se shower and eye bath. Thallium lodide Not set upThallium Bromide Not set up0Control parameters: (cel):0.1 mg/m3 in 8 hour Time Weighted Average (TWA)0.1 mg/m3 in 8 hour Time Weighted Average (TWA)Exposure controls:Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or se glasses with side shields are required if there is possibility of chipping or dust creation. Respirators mux worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation.9.Physical and chemicalAppearance: Flash point:Red geometric shapes, no odor.
including any incompatibilities: strong bases. Specific end uses: Optical Material for Manufacture of Optical Component Optical Material for Manufacture of Optical Component workers should not be exposed directly. Also install se shower and eye bath. personal protection Exposure Install a closed system or local exhaust as possible so workers should not be exposed directly. Also install se shower and eye bath. Control parameters: Occupational exposure limits (oel): Thallium lodide Thallium Bromide Veighted Average (TWA) Veighted Average (TWA) Weighted Average (TWA) Weighted Average (TWA) Exposure controls: Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or se glasses with side shields are required if there is possibility of chipping or dust creation. Respirators mut worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation. Notal exhaust ventilation. 9. Physical and chemical Appearance: Flash point: Red geometric shapes, no odor.
Specific end uses: Optical Material for Manufacture of Optical Component 8. Exposure controls / personal protection Engineering controls: Install a closed system or local exhaust as possible so workers should not be exposed directly. Also install si shower and eye bath. Thallium protection Control parameters: Not set up Not set up Occupational exposure limits (oel): Controls: Not set up 0.1 mg/m3 in 8 hour Time Weighted Average (TWA) Exposure controls: Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or si glasses with side shields are required if there is possibility of chipping or dust creation. Respirators mu- worm when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation. Not applicable 9. Physical and chemical Appearance: Flash point: Red geometric shapes, no odor.
8. Exposure controls / personal protection Engineering controls: Install a closed system or local exhaust as possible so workers should not be exposed directly. Also install so shower and eye bath. 7 Thallium lodide Thallium Bromide 8. Control parameters: 0.1 mg/m3 in 8 hour Time (oel): Not set up 9. Physical and chemical Appearance: Flash point: Protection
controls / personal protectionworkers should not be exposed directly. Also install sa shower and eye bath.protectionControl parameters: Occupational exposure limits (oel):Thallium lodide Not set upThallium Bromide Not set upOccupational exposure limits (oel):O.1 mg/m3 in 8 hour Time Weighted Average (TWA)0.1 mg/m3 in 8 hour Time Weighted Average (TWA)Exposure controls:Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or sa glasses with side shields are required if there is possibility of chipping or dust creation. Respirators mus worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation.9.Physical and chemicalAppearance: Flash point:Red geometric shapes, no odor.
personal shower and eye bath. protection Thallium lodide Control parameters: Not set up Occupational exposure limits 0.1 mg/m3 in 8 hour Time (cel): 0.1 mg/m3 in 8 hour Time Exposure controls: Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or se glasses with side shields are required if there is possibility of chipping or dust creation. Respirators mutworn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation. Vash hands immediately after handling the product. 9. Physical and chemical Appearance: Red geometric shapes, no odor. Prostable Flash point: Not Applicable Not Applicable
protectionThallium lodideThallium BromideControl parameters: Occupational exposure limits (oel):Not set up0.1 mg/m3 in 8 hour Time Weighted Average (TWA)0.1 mg/m3 in 8 hour Time Weighted Average (TWA)Exposure controls:Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or sa glasses with side shields are required if there is possibility of chipping or dust creation. Respirators musi worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation.9.Physical and chemicalAppearance: Flash point:Red geometric shapes, no odor. Not Applicable
Provide adequate general mechanical ventilation, local exhaust ventilation. Not set up Not set up 9. Physical and chemical Appearance: Red geometric shapes, no odor. 9. Physical and chemical Appearance: Red geometric shapes, no odor.
Occupational exposure limits (oel): 0.1 mg/m3 in 8 hour Time Weighted Average (TWA) 0.1 mg/m3 in 8 hour Weighted Average (TWA) Exposure controls: Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or sa glasses with side shields are required if there is possibility of chipping or dust creation. Respirators must worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation. National exposure 9. Physical and chemical Appearance: Flash point: Red geometric shapes, no odor.
(oel): Weighted Average (TWA) Weighted Average (TWA) Exposure controls: Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or sa glasses with side shields are required if there is possibility of chipping or dust creation. Respirators must worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation. Wash hands immediately after handling the product. 9. Physical and chemical Appearance: Red geometric shapes, no odor. Not Applicable Not Applicable Not Applicable
Exposure controls: Protective gloves made of PVA are required. Use laboratory coat is suggested. Safety goggles or sa glasses with side shields are required if there is possibility of chipping or dust creation. Respirators must worn when the threshold limit is exceeded.
9. Physical and chemical 9. Physical and chemical Appearance: Red geometric shapes, no odor. Not Applicable
glasses with side shields are required if there is possibility of chipping or dust creation. Respirators must worn when the threshold limit is exceeded. Provide adequate general mechanical ventilation, local exhaust ventilation. 9. Physical and chemical Appearance: Flash point: Red geometric shapes, no odor. Not Applicable
9. Physical and chemical Appearance: Red geometric shapes, no odor. 9. Physical and chemical Appearance: Red geometric shapes, no odor.
9. Physical and chemical Appearance: Red geometric shapes, no odor. 9. Physical and chemical Appearance: Red geometric shapes, no odor.
Provide adequate general mechanical ventilation, local exhaust ventilation. Vash hands immediately after handling the product. Provide adequate general mechanical ventilation, local exhaust ventilation. Wash hands immediately after handling the product. Physical and chemical Appearance: Red geometric shapes, no odor. Not Applicable
9. Physical and chemical Appearance: Flash point: Red geometric shapes, no odor.
9. Physical and chemical Appearance: Red geometric shapes, no odor. Not Applicable
9. Physical and chemical Appearance: Red geometric shapes, no odor. Vertical Flash point: Not Applicable
chemical Flash point: Not Applicable
properties Boiling point (760mm hg): Not Applicable
Flammability: Not Applicable
Melting point: 414 deg. C
Explosive properties: Not Applicable
Specific gravity: 7.37 g/mL
Vapor pressure: Negligible at 25 deg. C
Solubility in water: Low Solubility: 50mg/100ml H2O at 20 deg. C
pH in aqueous solution: Not determined
10. Stability and Reactivity: Reacts with strong oxidizing materials
reactivity Chemical stability: Stable under normal conditions of storage and use
Possibility of hazardous None known
reactions:
Conditions to avoid: Can react with oxidizing agents. Avoid strong acids
Incompatible materials: Strong Mineral Acids. Strong oxidizing materials
Hazardous decomposition Thallium, Hydrogen lodide, Hydrogen Bromide.
products:
products: 11. Toxicological Information on toxicological Extremely toxic by ingestion, with a cumulative effect.
11. Toxicological Information on toxicological Extremely toxic by ingestion, with a cumulative effect.
11. Toxicological information Information on toxicological effects Extremely toxic by ingestion, with a cumulative effect. Affects nervous system, skin and cardiovascular system

			Particular care must be exercised when machining and
			creating dust or particles. Inhalation of dust may irritate
			respiratory system.
		Toxic dose - Id50:	24 mg/kg oral
		Carcinogenicity:	No evidence of carcinogenic properties.
		Mutagenicity/teratogenicity:	Evidence of reproductive effects.
12.	Ecological	Toxicity:	Danger to drinking water. Poisonous to Fish
	information	Persistence and degradability:	No Data
		Bioaccumulative potential:	No Data
		Mobility in soil:	No Data
		Results of pbt and vpvb	Not required or conducted
		assessment:	
		Other adverse affects:	Do not allow product to reach ground water, water course
			or sewage system. Only release to environment with
			proper government permit.
13.	Disposal	Waste treatment methods	Chemical residues are generally classified as special
	considerations		waste, and are covered by regulations which vary
			according to location.
			Contact your local waste disposal authority for advice, or
			pass to a chemical disposal company.
14.	Transport	IMDG	Comply with IMO
	information	Un number:.	1707
		Un proper shipping name:	Thallium Compounds, N.O.S. (Thallium Bromide-Iodide).
		Transport hazard class::	6.1
		Packing group:	11
		Marine Pollutant:	Р
		Harmful Liquid	Not Applicable
		Substances:	FF
		IATA	Comply with ICAO/IATA
		Un number:.	1707
		Un proper shipping name:	Thallium Compounds, N.O.S. (Thallium Bromide-Iodide).
		Transport hazard class::	6.1
		Packing group:	
15.	Regulatory	Safety, health and	TSCA: Listed in the TSCA inventory
.0.	. logulatory	5.	
	information	environmental regulations /	SARA: Listed. This product is subject to SARA section 313
	information	environmental regulations /	SARA: Listed. This product is subject to SARA section 313 reporting requirement – thallium compounds.
	information	legislation specific for the	reporting requirement – thallium compounds.
	information		reporting requirement – thallium compounds. WHMIS: This is a controlled product under the Canadian
16		legislation specific for the	reporting requirement – thallium compounds.
16.	information Other information	legislation specific for the	reporting requirement – thallium compounds. WHMIS: This is a controlled product under the Canadian

• This SDS was prepared sincerely on the basis of the information we could obtained, however, any warranty shall not be given regarding the data contained and the assessment of hazards and toxicity. Prior to use, please investigate not only the hazards and toxicity information but also the laws and regulations of the organization, area and country where the products are to be used, which shall be given the first priority.

- Some new information or amendments may be added later. If you have any questions, please feel free to contact us.
- The stated cautions are for normal handling only. In case of special handling, sufficient care should be taken, in addition to the safety measures suitable for the situation. All chemical products should be treated with the recognition of "having unknown hazards and toxicity", which differ greatly depending on the conditions and handling when in use and/or the conditions and duration of storage. The products must be handled only by those who are familiar with specialized knowledge and have experience or under the guidance of those specialists throughout use from opening to storage and disposal. Safe usage conditions shall be set up on each user's own responsibility.